



Silage Compaction Rollers SILO KOMPAKT rigid

Technical data	SK 200 ST	SK 250 ST	SK 300 ST
Frame	rigid	rigid	rigid
Wide	2.000 mm	2.500 mm	3.000 mm
Total roll diameter	940 mm	940 mm	940 mm
Number of discs	10	12	14
basic weight	approx. 1,310 kg	approx. 1,530 kg	approx. 1,710 kg
additional weight by waterfilling (standard equipment)	approx. 500 kg	approx. 600 kg	approx. 700 kg
maximum weight (only reachable with extra equipment)	approx. 1,850 kg	approx. 3,170 kg	approx. 3,450 kg
Attachment	Three-point Cat. 2, 3 & 4	Three-point Cat. 2 & Cat. 3	Three-point Cat. 2, 3 & 4

Silage Compaction Rollers SILO KOMPAKT hydraulically moveable

Technical data	SK 250 H	SK 300 H
Frame	movable 500 mm to the left & right	movable 500 mm to the left & right
Wide	2.500 mm	3.000 mm
Total roll diameter	940 mm	940 mm
Number of discs	12	14
basic weight	approx. 1,740 kg	approx. 1,920 kg
additional weight by waterfilling (standard equipment)	approx. 600 kg	approx. 700 kg
maximum weight (only reachable with extra equipment)	approx. 3,380 kg	approx. 3,660 kg
Attachment	Three-point Cat. 2, 3 & 4	Three-point Cat. 2, 3 & 4