



Concrete mixer TURBO MIX

	TURBO MIX					TURBO MIX SF	
Technical Data	TM 95	TM 125	TM 150	TM 180	TM 200	TM 125 SF	TM 150 SF
Working capacity – with concrete	240 l	500 l	750 l	1000 l	1200 l	500 l	750 l
Capacity with lighter loads - without light mix adaptor	320 l	700 l	940 l	1200 l	1400 l	700 l	940 l
Capacity with lighter loads - with light mix adaptor	-	850 l	1230 l	1500 l	1720 l	-	-
Drum diameter	950 mm	1250 mm	1500 mm	1800 mm	2000 mm	1250 mm	1500 mm
Drum height	500 mm	625 mm	625 mm	625 mm	625 mm	625 mm	625 mm
Type of drive	PTO drive	PTO drive	PTO drive	PTO drive	PTO drive	PTO drive	PTO drive
Power requirement	mix + drive from 20 HP	mix + drive from 50 HP	mix + drive from 80 HP	mix + drive from 100 HP	mix + drive from 120 HP	mix + drive from 70 HP	mix + drive from 90 HP
Weight	approx. 280 kg	approx. 350 kg	approx. 450 kg	approx. 510 kg	approx. 580 kg	approx. 580 kg	approx. 680 kg
Spring-mounted mixing tines	3 pcs.	4 pcs.	4 pcs.	4 pcs.	5 pcs.	4 pcs.	4 pcs.
Output concrete	approx. 4 m ³ / h	approx. 8 m ³ / h	approx. 13 m ³ / h	approx. 15 m ³ / h	approx. 17 m ³ / h	approx. 8 m ³ / h	approx. 13 m ³ / h
Number of sliders	1 pcs mechanical	1 pcs mechanical	1 pcs mechanical	1 pcs mechanical	1 pcs mechanical	1 pcs mechanical	1 pcs mechanical
Slide	rigid	180° swiveling	180° swiveling	180° swiveling	180° swiveling	rigid	rigid



Special concrete mixer

	Special concrete mixer			KOMBI MIX
Technical data	TM 95 E	TM 125 P	TM 150 P	KM 150 2S
Working capacity – with concrete	240 l	500 l	750 l	800 l
Capacity with lighter loads - without light mix adaptor	320 l	700 l	940 l	940 l
Capacity with lighter loads - with light mix adaptor	-	850 l	1230 l	1230 l
Drum diameter	950 mm	1250 mm	1500 mm	1500 mm
Drum height	500 mm	625 mm	625 mm	625 mm
Type of drive	Electric motor 4,5 kW	Electric motor 7,5 kW	Electric motor 9,5 kW	PTO drive
Power requirement	16 amp / 400 V	32 amp / 400 V	32 amp / 400 V	mix + drive from 80 hp
Weight	approx. 300 kg	approx. 620 kg	approx. 690 kg	approx. 500 kg
Spring-mounted mixing tines	3 pcs.	4 pcs.	4 pcs.	4 pcs.
Working capacity – with concrete	approx. 4 m ³ / h	approx. 8 m ³ / h	approx. 13 m ³ / h	approx. 13 m ³ / h
Number of sliders	1 pcs. mechanical	1 pcs. mechanical	1 pcs. mechanical	1 pcs. mechanical
Slide	rigid	180 ° swiveling	180 ° swiveling	180 ° swiveling
Capacity - bags/hour	-	-	-	approx. 1200
Number of filling spouts	-	-	-	2
Minimum sandbags	-	-	-	30 x 60 cm

Special concrete mixer: SPECIAL MODELS

Individual fabrications according to your wishes

Customer satisfaction is our top priority. For this very reason, we offer the possibility of individually adapting the most diverse concrete mixer models to your requirements and thus making the mixing operation even more effective. If you also have individual ideas and suggestions, we look forward to your inquiry at any time - step by step, we plan the "concrete mixer as desired" together with you.

Simply call +43 (0) 7757 6701 or send an e-mail to office@mammut.at
We will also find the ideal solution for your needs!